



Technical fluids - Aerosols

Eurol Penetrating Oil Spray 400ML

Universal penetrating oil

Description

Eurol Penetrating Oil Spray is a high quality, effective aid for loosening rusted parts.

Eurol Penetrating Oil Spray has, besides good penetrating properties, a corrosion resistant properties.

Eurol Penetrating Oil Spray contains graphite and molybdenum disulfide (MoS₂) which ensures long lasting lubrication.

Eurol Penetrating Oil Spray can be used at applications such as:

- Hinges and locks
- Screw connections
- Gears
- Mountings (screws, bolts and nuts)
- Tools

Eurol Penetrating Oil Spray must be shaken well before use. Spray at approx. 20-25 cm from the object. Apply the desired quantity. The Product has to act for 5 to 10 minutes.

Use Eurol Penetrating Oil Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water. Flammable substance.

Eurol Penetrating Oil Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

Physical properties

Colour	Yellow	
Flash point	-20 °C	ASTM D 93

Article number E701300
Version 1.1, 18-06-2019

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.